

## Two Way Intercoms with motion- Detection

### Descriptions:

The super cam requires a chime box for most of the features to work. Up to two cameras can be used with one chimebox.

There's a reason it's called the SuperCam - this little camera does it all. Place the unit at an entrance or anywhere else you want to monitor. You'll be alerted to any motion and you can have a two-way conversation through the intercom, (requires Chimebox).



### Features:

- Built-in speaker and indoor enunciator box enables 2-way communication (requires Chimebox).
- Built-in motion detector alerts you to movement within the protected area, visually and audibly (requires optional Chime Box)
- Plug 'n' play installation
- Durable weatherproof construction - use it indoors or out

### Specifications:

TV System	EIA (Black & White) Standard
Integrated Lens:	3.60mm, F2.0 Fixed Focus
Resolution:	360 Horizontal TVL
Signal/Noise Ratio:	48dB
Image Sensor:	1/3" CCD
High Speed Electronics Shutter:	1/60 – 80,000 sec
Current Consumption:	Approx 100mA
Dimensions:	2.8"W x 3.0"H x 3.5"D

## Wired Video Door Phone System with 2-Way Intercom

# DOORPHONE

### Wired Video Door Phone System

Great for the home or office, this door phone system works great outside where there is little to no available lighting.



This two-piece system is easy to install at your front door or entryway. It helps make answering the door easy and safe because you can see, hear, and talk to who is there without having to open the door.

The Monitor/Handset unit mounts inside the building and plugs into the wall for power, the Camera/Speaker unit mounts on the outside and is connected to the monitor by 2 wires. You can use your existing doorbell wire or run the included wire. When someone rings the built-in doorbell, the monitor comes on and the intercom is activated.

The camera can be aimed once it is mounted and has built-in Infrared illuminators that can see up to 6' away in complete darkness. Options include extra cameras and monitors and a new color system.

This camera includes mini wall mount, wall power cord, and handset/monitor. 1 year parts and labor warranty included.

#### Features:

- 1/3" CCD imaging device for camcorder quality video.
- No moving parts for better reliability.
- 90° Field of view for better area coverage.
- Handset monitor for two-way intercom.
- Standard 1 year parts and labor warranty.

## Technical Specifications:

### PVDOORPHONE Black and White Camera Specifications:

<b>Resolution:</b>	420 TV Lines
<b>Lens:</b>	f3.8mm lens with 90° field of view (diagonal)
<b>Low light compensation:</b>	0.0 lux f2.0
<b>Power requirements:</b>	Max 2.5 watts
<b>Camera Dimensions:</b>	5"(H) X 3-3/4"(W) X 3/4"(D)
<b>Camera iris:</b>	ELC light compensation
<b>Electronic Shutter:</b>	1/60~1/10,000,000 Sec. Automatic
<b>Imaging Device:</b>	1/3" CCD Grade 1st
<b>Scanning System:</b>	2:1 Interlace
<b>S/N Ratio:</b>	More than 50dB
<b>Signal System:</b>	E:EIA 60Hz
<b>Operating Temperature:</b>	-10°C~50°C
<b>Warranty:</b>	1 Year parts and labor warranty (standard)

---

<b>Monitor:</b>	4" Flat Tube
<b>Power requirements:</b>	Max 12W standby 2W
<b>Monitor Dimensions:</b>	8-1/4"(H) X 7-1/4"(W) X 2"(D)
<b>Communication System:</b>	Duplex Handset
<b>Call Signaling Device:</b>	Door Chime
<b>Wiring:</b>	2 Wire
<b>Max Wiring Distance:</b>	150' with 22 gauge 300' with RG 59U
<b>Warranty:</b>	1 Year parts and labor warranty (standard)

## Included Accessories:

### **PS12V**

Camera Power Supply



## Optional Accessories:

### **MINIMOD1**

Single Channel Audio/Video TV Modulator for viewing Video on the channel of your choice on all of the TV's in the home.



### **DOORPHONESLAVEMON**

Additional slave monitor for multiple handset locations.



### **DOORPHONECAM**

Additional camera for multiple entrances expandable up to 2 cameras.

